

DSKE 120 - 180




Standard Equipment

- 3 points ISO universal hitch with 1st/2nd category fork
- Gearbox with free wheel 540'
- Gearbox in external position of the machine
- Rear roller adjustable in height
- Hydraulic cylinder for machine tilting
- Hydraulic cylinder for lateral displacement
- Closed shredding chamber for material internal discharge
- Direct cardan shaft (tractor side fork 1" 3/8 Z6)
- Front protection flaps
- EC guard kit



VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale
Via dell'Industria, 27/A
36045 Alonte (VI) - ITALY
Tel. +39 0444 436247
Fax +39 0444 436237
www.vigolo.com - info@vigolo.com



Supporto sagomato
Shaped lug
Profilerter Träger
Support profilé



Mod.	 Lavoro mm	 Ingombro mm	HP  min - max	Kg 				
DSKE 120	1200	1550	30 - 80	400	14	40	20	3
DSKE 140	1400	1750	30 - 80	430	16	48	24	3
DSKE 160	1600	1950	35 - 80	470	18	56	28	4
DSKE 180	1800	2150	40 - 80	500	20	60	30	4

VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale
Via dell'Industria, 27/A
36045 Alonte (VI) - ITALY
Tel. +39 0444 436247
Fax +39 0444 436237
www.vigolo.com - info@vigolo.com