

RSA/R MAX 180 - 320



Standard Equipment

- 3 points ISO universal hitch with 2nd category fork, double headstock for front and rear use
- Gearbox with free wheel 1000', 2 pto, mod. Vigolo L810 (RSA/R MAX 180÷250)
- Gearbox with free wheel 1000', 2 pto, mod. Vigolo E810 (RSA/R MAX 280÷320)
- Arrangement for version 540' with inversion of the pulleys
- Reinforced double frame
- Triple counter-knife
- Hydraulic side shift through double tube of headstock
- Rear roller adjustable in height with scraper, increased bearings
- Front rounded and flattened side
- Direct cardan shaft (tractor side fork 1" 3/8 Z6)
- Front protection flaps
- EC guard kit



VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale
Via dell'Industria, 27/A
36045 Alonte (VI) - ITALY
Tel. +39 0444 436247
Fax +39 0444 436237
www.vigolo.com - info@vigolo.com

RSA/R Max 180-300 RSA/R Max 320





Fiancata arrotondata
Rounded side
Abgerundetes Gehäuse
Côté arrondie



Supporto forgiato
Cast lug
Geschmiedeter Träger
Support forgé



Mod.	 Lavoro mm	 Ingombro mm	 HP min - max	 Kg				
RSA/R Max 180	1800	1990	40 - 120	840	16	32 + 16	± 200	5
RSA/R Max 200	2000	2190	50 - 120	890	18	36 + 18	± 200	5
RSA/R Max 220	2200	2390	50 - 120	960	20	40 + 20	± 200	5
RSA/R Max 250	2500	2690	60 - 120	1030	22	44 + 22	± 200	5
RSA/R Max 280	2800	2990	70 - 180	1100	24	48 + 24	± 200	6
RSA/R Max 300	3000	3190	80 - 180	1170	28	56 + 28	± 200	6
RSA/R Max 320	3200	3390	80 - 180	1200	32	64 + 32	± 200	6

VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale
Via dell'Industria, 27/A
36045 Alonte (VI) - ITALY
Tel. +39 0444 436247
Fax +39 0444 436237
www.vigolo.com - info@vigolo.com