
































































Cat.	Mod.																					
		Lavoro mm	Ingombro mm		HP min - max	Kg	Categoria 3° punto	Giri rotore 540°	Giri rotore 1000°	Numero cinghie	931060004	931040003	931060002	931060001	931040013	931060005	931040018 (x2) 931990016	Diametro del rotore	Diametro del rullo	Ruote anteriori fisse in ferro	Ruote posteriori girevoli in gomma	Kit tabelle stradali
TK2	TK2 100	1000	1125	± 125	25-80	240	1°	2590	2500	2	12	32	16	-	-	-	-	130	114	-	-	○
	TK2 120	1200	1325	± 125	25-80	260	1°	2590	2500	2	14	40	20	-	-	-	-	130	114	-	-	○
	TK2 140	1400	1525	± 125	30-80	290	1°	2590	2500	3	16	48	24	-	-	-	-	130	114	○	○	○
	TK2 150	1500	1625	± 125	30-80	300	1°	2590	2500	3	16	52	26	-	-	-	-	130	114	○	○	○
	TK2 160	1600	1725	± 125	30-80	320	1°	2590	2500	3	18	56	28	-	-	-	-	130	114	○	○	○
	TK2 180	1800	1925	± 125	40-80	350	1°	2590	2500	4	20	60	30	-	-	-	-	130	114	○	○	○
	TK2 200	2000	2125	± 125	40-80	370	1°	2590	2500	4	22	64	32	-	-	-	-	130	114	○	○	○






















TK2/R	TK2/R 100	1000	1125	± 125	25-80	270	1°	2590	2500	2	12	32	16	-	-	-	-	130	114	-	-	○
	TK2/R 120	1200	1325	± 125	25-80	280	1°	2590	2500	2	14	40	20	-	-	-	-	130	114	-	-	○
	TK2/R 140	1400	1525	± 125	30-80	310	1°	2590	2500	3	16	48	24	-	-	-	-	130	114	○	-	○
	TK2/R 150	1500	1625	± 125	30-80	330	1°	2590	2500	3	16	52	26	-	-	-	-	130	114	○	-	○
	TK2/R 160	1600	1725	± 125	30-80	350	1°	2590	2500	3	18	56	28	-	-	-	-	130	114	○	-	○
	TK2/R 180	1800	1925	± 125	40-80	380	1°	2590	2500	4	20	60	30	-	-	-	-	130	114	○	-	○
	TK2/R 200	2000	2125	± 125	40-80	410	1°	2590	2500	4	22	64	32	-	-	-	-	130	114	○	-	○

MU2	MU2 100	1000	1110	± 125	25-100	355	1°	2280	2140	2	-	-	18	8	24	-	-	150	154	-	-	○
	MU2 120	1200	1310	± 125	30-100	400	1°	2280	2140	2	-	-	22	10	28	-	-	150	154	-	-	○
	MU2 140	1400	1510	± 125	30-100	420	1°	2280	2140	3	-	-	26	12	32	-	-	150	154	○	○	○
	MU2 150	1500	1640	± 200	40-100	450	1° / 2°	2280	2140	3	-	-	28	14	36	-	-	150	154	○	○	○
	MU2 160	1600	1740	± 200	40-100	470	1° / 2°	2280	2140	3	-	-	30	14	36	-	-	150	154	○	○	○
	MU2 180	1800	1970	± 250	40-100	505	1° / 2°	2280	2140	4	-	-	34	16	40	-	-	150	154	○	○	○
	MU2 200	2000	2170	± 250	40-100	530	1° / 2°	2280	2140	4	-	-	38	18	44	-	-	150	154	○	○	○
	MU2 220	2200	2370	± 250	50-100	600	1° / 2°	2280	2140	4	-	-	40	20	48	-	-	150	154	○	○	○
	MU2 250	2500	2670	± 250	60-100	660	1° / 2°	2280	2140	5	-	-	48	22	56	-	-	150	154	○	○	○
MU2 280	2800	2980	± 250	60-100	730	1° / 2°	2280	2140	5	-	-	52	24	64	-	-	194	194	○	○	○	

MU2/R	MU2/R 100	1000	1110	± 125	25-100	455	1°	2280	2140	2	-	-	18	8	8	-	-	150	154	-	-	○
	MU2/R 120	1200	1310	± 125	30-100	500	1°	2280	2140	2	-	-	22	10	10	-	-	150	154	-	-	○
	MU2/R 140	1400	1510	± 125	30-100	520	1°	2280	2140	3	-	-	26	12	12	-	-	150	154	○	-	○
	MU2/R 150	1500	1640	± 200	40-100	550	1° / 2°	2280	2140	3	-	-	28	14	14	-	-	150	154	○	-	○
	MU2/R 160	1600	1740	± 200	40-100	570	1° / 2°	2280	2140	3	-	-	30	14	14	-	-	150	154	○	-	○
	MU2/R 180	1800	1970	± 250	40-100	605	1° / 2°	2280	2140	4	-	-	34	16	16	-	-	150	154	○	-	○
	MU2/R 200	2000	2170	± 250	40-100	630	1° / 2°	2280	2140	4	-	-	38	18	18	-	-	150	154	○	-	○
	MU2/R 220	2200	2370	± 250	50-100	700	1° / 2°	2280	2140	4	-	-	40	20	20	-	-	150	154	○	-	○
	MU2/R 250	2500	2670	± 250	60-100	760	1° / 2°	2280	2140	5	-	-	48	22	22	-	-	150	154	○	-	○
MU2/R 280	2800	2980	± 250	60-100	830	1° / 2°	2280	2140	5	-	-	52	24	24	-	-	194	194	○	-	○	

Cat.	Mod.																					
		Lavoro mm	Ingombro mm	±	HP min - max	Kg	Categoria 3° punto	Giri rotore 540°	Giri rotore 1000°	Numero cinghie	931060004	931040003	931060002	931060001	931040013	931060005	931040018 (x2) 931990016	Diametro del rotore	Diametro del rullo	Ruote anteriori fisse in ferro	Ruote posteriori girevoli in gomma	Kit tabelle stradali
TSA/L	TSA/L 100	1000	1135	± 125	30-100	380	1°	2280	2140	2	-	-	18	8	24	-	-	150	154	-	-	○
	TSA/L 120	1200	1335	± 125	30-100	420	1°	2280	2140	2	-	-	22	10	28	-	-	150	154	-	-	○
	TSA/L 140	1400	1535	± 125	30-100	450	1°	2280	2140	3	-	-	26	12	32	-	-	150	154	○	○	○
	TSA/L 150	1500	1635	± 200	40-100	480	2°	2280	2140	3	-	-	28	14	36	-	-	150	154	○	○	○
	TSA/L 160	1600	1765	± 200	40-100	520	2°	2280	2140	3	-	-	30	14	36	-	-	150	154	○	○	○
	TSA/L 180	1800	1965	± 200	40-100	550	2°	2280	2140	4	-	-	34	16	40	-	-	150	154	○	○	○
	TSA/L 200	2000	2165	± 200	50-100	600	2°	2280	2140	4	-	-	38	18	44	-	-	150	154	○	○	○
	TSA/L 220	2200	2365	± 200	50-100	660	2°	2280	2140	4	-	-	40	20	48	-	-	150	154	○	○	○
	TSA/L 250	2500	2665	± 200	60-100	720	2°	2280	2140	5	-	-	48	22	56	-	-	150	154	○	○	○
TSA/LR	TSA/LR 100	1000	1135	± 125	30-100	430	1°	2280	2140	2	-	-	18	8	24	-	-	150	154	-	-	○
	TSA/LR 120	1200	1335	± 125	30-100	470	1°	2280	2140	2	-	-	22	10	28	-	-	150	154	-	-	○
	TSA/LR 140	1400	1535	± 125	30-100	500	1°	2280	2140	3	-	-	26	12	32	-	-	150	154	○	-	○
	TSA/LR 150	1500	1635	± 150	40-100	530	2°	2280	2140	3	-	-	28	14	36	-	-	150	154	○	-	○
	TSA/LR 160	1600	1765	± 150	40-100	570	2°	2280	2140	3	-	-	30	14	36	-	-	150	154	○	-	○
	TSA/LR 180	1800	1965	± 200	40-100	600	2°	2280	2140	4	-	-	34	16	40	-	-	150	154	○	-	○
	TSA/LR 200	2000	2165	± 200	50-100	650	2°	2280	2140	4	-	-	38	18	44	-	-	150	154	○	-	○
	TSA/LR 220	2200	2365	± 200	50-100	710	2°	2280	2140	4	-	-	40	20	48	-	-	150	154	○	-	○
	TSA/LR 250	2500	2665	± 200	60-100	770	2°	2280	2140	5	-	-	48	22	56	-	-	150	154	○	-	○
TSA/P	TSA/P 180	1800	1970	± 200	50-120	650	2°	2280	2140	5	-	-	34	16	40	-	-	194	194	○	○	○
	TSA/P 200	2000	2170	± 200	50-120	700	2°	2280	2140	5	-	-	38	18	44	-	-	194	194	○	○	○
	TSA/P 220	2200	2370	± 200	50-120	760	2°	2280	2140	5	-	-	40	20	48	-	-	194	194	○	○	○
	TSA/P 250	2500	2670	± 200	60-120	830	2°	2280	2140	5	-	-	48	22	56	-	-	194	194	○	○	○
	TSA/P 280	2800	2990	± 200	70-180	910	2°	2280	2140	6	-	-	52	24	64	-	-	194	194	○	○	○
	TSA/P 300	3000	3190	± 200	80-180	1000	2°	2280	2140	6	-	-	56	28	68	-	-	194	194	○	○	○
TSA/PR	TSA/PR 180	1800	1970	± 200	50-120	700	2°	2280	2140	5	-	-	34	16	40	-	-	194	194	○	-	○
	TSA/PR 200	2000	2170	± 200	50-120	750	2°	2280	2140	5	-	-	38	18	44	-	-	194	194	○	-	○
	TSA/PR 220	2200	2370	± 200	50-120	810	2°	2280	2140	5	-	-	40	20	48	-	-	194	194	○	-	○
	TSA/PR 250	2500	2670	± 200	60-120	880	2°	2280	2140	5	-	-	48	22	56	-	-	194	194	○	-	○
	TSA/PR 280	2800	2990	± 200	70-180	960	2°	2280	2140	6	-	-	52	24	64	-	-	194	194	○	-	○
	TSA/PR 300	3000	3190	± 200	80-180	1040	2°	2280	2140	6	-	-	56	28	68	-	-	194	194	○	-	○

Cat.	Mod.	 Lavoro	 Ingombro		 HP min - max	 Kg	 Categoria 3° punto	 540° Giri rotore	 1000° Giri rotore	 Numero cinghie	 931060004	 931040003	 931060002	 931060001	 931040013	 931060005	 931040018 (x2) 931990016	 Diametro del rotore	 Diametro del rullo	 Ruote anteriori fisse in ferro	 Ruote posteriori girevoli in gomma	 Kit tabelle stradali
MX	MX 200	2000	2170	± 250	60 - 120	790	2°	2280	2140	5	-	-	38	18	44	-	-	194	194	○	○	○
	MX 220	2200	2370	± 250	60 - 120	820	2°	2280	2140	5	-	-	40	20	48	-	-	194	194	○	○	○
	MX 250	2500	2670	± 250	70 - 120	890	2°	2280	2140	5	-	-	48	22	56	-	-	194	194	○	○	○
	MX 280	2800	2990	± 250	80 - 150	960	2°	2280	2140	6	-	-	52	24	64	-	-	194	194	○	○	○
	MX 300	3000	3190	± 250	90 - 150	1030	2°	2280	2140	6	-	-	56	28	68	-	-	194	194	○	○	○
MX/R	MX/R 200	2000	2170	± 250	60 - 120	870	2°	2280	2140	5	-	-	38	18	44	-	-	194	194	○	-	○
	MX/R 220	2200	2370	± 250	60 - 120	900	2°	2280	2140	5	-	-	40	20	48	-	-	194	194	○	-	○
	MX/R 250	2500	2670	± 250	70 - 120	970	2°	2280	2140	5	-	-	48	22	56	-	-	194	194	○	-	○
	MX/R 280	2800	2990	± 250	80 - 150	1010	2°	2280	2140	6	-	-	52	24	64	-	-	194	194	○	-	○
	MX/R 300	3000	3190	± 250	90 - 150	1110	2°	2280	2140	6	-	-	56	28	68	-	-	194	194	○	-	○
RSA Plus	RSA Plus 160	1600	1770	± 250	40-120	630	2°	2280	2140	5	-	-	30	-	-	14	28 + 14	160	194	○	○	○
	RSA Plus 180	1800	1970	± 250	40-120	680	2°	2280	2140	5	-	-	34	-	-	16	32 + 16	160	194	○	○	○
	RSA Plus 200	2000	2170	± 250	50-120	730	2°	2280	2140	5	-	-	38	-	-	18	36 + 18	160	194	○	○	○
	RSA Plus 220	2200	2370	± 250	50-120	800	2°	2280	2140	5	-	-	40	-	-	20	40 + 20	160	194	○	○	○
	RSA Plus 250	2500	2670	± 250	60-120	870	2°	2280	2140	5	-	-	48	-	-	22	44 + 22	160	194	○	○	○
RSA/R Plus	RSA/R Plus 160	1600	1770	± 200	40-120	680	2°	2280	2140	5	-	-	30	-	-	14	28 + 14	160	194	○	-	○
	RSA/R Plus 180	1800	1970	± 200	40-120	730	2°	2280	2140	5	-	-	34	-	-	16	32 + 16	160	194	○	-	○
	RSA/R Plus 200	2000	2170	± 200	50-120	780	2°	2280	2140	5	-	-	38	-	-	18	36 + 18	160	194	○	-	○
	RSA/R Plus 220	2200	2370	± 200	50-120	850	2°	2280	2140	5	-	-	40	-	-	20	40 + 20	160	194	○	-	○
	RSA/R Plus 250	2500	2670	± 200	60-120	920	2°	2280	2140	5	-	-	48	-	-	22	44 + 22	160	194	○	-	○

Cat.	Mod.																					
		Lavoro mm	Ingombro mm		HP min - max	Kg	Categoria 3° punto	Giri rotore 540°	Giri rotore 1000°	Numero cinghie	931060004	931040003	931060002	931060001	931040013	931060005	931040018 (x2) 931990016	Diametro del rotore	Diametro del rullo	Ruote anteriori fisse in ferro	Ruote posteriori girevoli in gomma	Kit tabelle stradali
RSA Max	RSA Max 180	1800	1990	± 250	40-120	790	2°	2280	2140	5	-	-	34	-	-	16	32 + 16	200	194	○	○	○
	RSA Max 200	2000	2190	± 250	50-120	840	2°	2280	2140	5	-	-	38	-	-	18	36 + 18	200	194	○	○	○
	RSA Max 220	2200	2390	± 250	50-120	910	2°	2280	2140	5	-	-	40	-	-	20	40 + 20	200	194	○	○	○
	RSA Max 250	2500	2690	± 250	60-120	980	2°	2280	2140	5	-	-	48	-	-	22	44 + 22	200	194	○	○	○
	RSA Max 280	2800	2990	± 250	70-180	1050	2°	1690	2000	6	-	-	52	-	-	24	48 + 24	200	194	○	○	○
	RSA Max 300	3000	3190	± 250	80-180	1120	2°	1690	2000	6	-	-	56	-	-	28	48 + 28	200	194	○	○	○
	RSA Max 320	3200	3390	± 250	80-180	1150	2°	1890	1780	6	-	-	58	-	-	32	64 + 32	220	194	○	○	○
RSA/R Max	RSA/R Max 180	1800	1990	± 200	40-120	840	2°	2280	2140	5	-	-	34	-	-	16	32 + 16	200	194	○	-	○
	RSA/R Max 200	2000	2190	± 200	50-120	890	2°	2280	2140	5	-	-	38	-	-	18	36 + 18	200	194	○	-	○
	RSA/R Max 220	2200	2390	± 200	50-120	960	2°	2280	2140	5	-	-	40	-	-	20	40 + 20	200	194	○	-	○
	RSA/R Max 250	2500	2690	± 200	60-120	1030	2°	2280	2140	5	-	-	48	-	-	22	44 + 22	200	194	○	-	○
	RSA/R Max 280	2800	2990	± 200	70-180	1100	2°	1690	2000	6	-	-	52	-	-	24	48 + 24	200	194	○	-	○
	RSA/R Max 300	3000	3190	± 200	80-180	1170	2°	1690	2000	6	-	-	56	-	-	28	48 + 28	200	194	○	-	○
	RSA/R Max 320	3200	3390	± 200	80-180	1200	2°	1890	1780	6	-	-	58	-	-	32	64 + 32	220	194	○	-	○
RSA Pick-Up	RSA Pick-Up 160	1600	1770	± 200	40-160	740	2°	2280	2140	5	-	-	-	-	-	14	-	160	194	○	○	○
	RSA Pick-Up 180	1800	1970	± 200	40-160	900	2°	2280	2140	5	-	-	-	-	-	16	-	160	194	○	○	○
	RSA Pick-Up 200	2000	2170	± 200	50-160	1060	2°	2280	2140	5	-	-	-	-	-	18	-	160	194	○	○	○
	RSA Pick-Up 220	2200	2370	± 200	50-160	1220	2°	2280	2140	5	-	-	-	-	-	20	-	160	194	○	○	○
	RSA Pick-Up 250	2500	2670	± 200	60-160	1380	2°	2280	2140	5	-	-	-	-	-	22	-	160	194	○	○	○
TK Hydro	TK Hydro 120	1200	1325		Portata Lt. 60	320		Giri rotore 2600		2	14	40	20	-	-	-	-	130	114	○	○	○
	TK Hydro 140	1400	1525		60	350		2600		2	16	48	24	-	-	-	-	130	114	○	○	○
	TK Hydro 160	1600	1725		60	380		2600		3	18	56	28	-	-	-	-	130	114	○	○	○
	TK Hydro 180	1800	1925		60	420		2600		3	20	60	30	-	-	-	-	130	114	○	○	○