




















Cat.	Mod.																			
		Lavoro mm	Ingombro mm	Standard	Opzionale	min - max	Kg	Categoria 3° punto	Giri rotore 540'	Numero cinghie	931060004	931040003	931060002	931060001	931040013	931060005	931040018 (x2) 931990016	Diametro del rotore	Diametro del rullo	Kit tabelle stradali
DSK	DSK 120	1200	1340	1640	1730	30 - 80	380	2°	2590	3	14	40	20	-	-	-	-	130	114	○
	DSK 140	1400	1540	1840	1930	30 - 80	410	2°	2590	3	16	48	24	-	-	-	-	130	114	○
	DSK 160	1600	1740	2040	2130	35 - 80	450	2°	2590	4	18	56	28	-	-	-	-	130	114	○
	DSK 180	1800	1940	2240	2330	40 - 80	480	2°	2590	4	20	60	30	-	-	-	-	130	114	○
DSKE	DSKE 120	1200	1550	1950	2080	30 - 80	400	2°	2590	3	14	40	20	-	-	-	-	130	114	○
	DSKE 140	1400	1750	2150	2280	30 - 80	430	2°	2590	3	16	48	24	-	-	-	-	130	114	○
	DSKE 160	1600	1950	2350	2480	35 - 80	470	2°	2590	4	18	56	28	-	-	-	-	130	114	○
	DSKE 180	1800	2150	2550	2680	40 - 80	500	2°	2590	4	20	60	30	-	-	-	-	130	114	○
LG2	LG2 120	1200	1390	1900	-	35 - 120	570	2°	2280	3	-	-	22	10	28	-	-	150	154	○
	LG2 140	1400	1590	2100	-	40 - 120	590	2°	2280	3	-	-	26	12	32	-	-	150	154	○
	LG2 160	1600	1790	2300	-	40 - 120	610	2°	2280	4	-	-	30	14	36	-	-	150	154	○
	LG2 180	1800	1990	2500	-	50 - 120	640	2°	2280	4	-	-	34	16	40	-	-	150	154	○
	LG2 200	2000	2190	2700	-	50 - 120	700	2°	2280	4	-	-	38	18	44	-	-	150	154	○
LGE2	LGE2 120	1200	1620	2250	-	35 - 120	590	2°	2280	3	-	-	22	10	28	-	-	150	154	○
	LGE2 140	1400	1820	2450	-	40 - 120	610	2°	2280	3	-	-	26	12	32	-	-	150	154	○
	LGE2 160	1600	2020	2650	-	40 - 120	630	2°	2280	4	-	-	30	14	36	-	-	150	154	○
	LGE2 180	1800	2220	2850	-	50 - 120	660	2°	2280	4	-	-	34	16	40	-	-	150	154	○
	LGE2 200	2000	2420	3050	-	50 - 120	720	2°	2280	4	-	-	38	18	44	-	-	150	154	○
SG2 / SGR2	SG2 160	1600	1790	2300	-	50 - 120	780	2°	2280	4	-	-	30	-	-	14	28 + 14	160	154	○
	SG2 180	1800	1990	2500	-	50 - 120	840	2°	2280	4	-	-	34	-	-	16	32 + 16	160	154	○
	SG2 200	2000	2190	2700	-	60 - 120	870	2°	2280	5	-	-	38	-	-	18	36 + 18	160	154	○
	SG2 220	2200	2390	2900	-	60 - 120	900	2°	2280	5	-	-	40	-	-	20	40 + 20	160	154	○
	SGR2 220	2200	2390	2900	-	70 - 200	980	3°	2360	5	-	-	40	-	-	20	40 + 20	160	154	○
	SGR2 250	2500	2690	3200	-	80 - 200	1100	3°	2360	5	-	-	48	-	-	22	44 + 22	160	154	○
SGE2 / SGR2	SGE2 160	1600	2080	2720	-	50 - 120	800	2°	2280	4	-	-	30	-	-	14	28 + 14	160	154	○
	SGE2 180	1800	2280	2920	-	50 - 120	860	2°	2280	4	-	-	34	-	-	16	32 + 16	160	154	○
	SGE2 200	2000	2480	3120	-	60 - 120	890	2°	2280	5	-	-	38	-	-	18	36 + 18	160	154	○
	SGE2 220	2200	2680	3320	-	60 - 120	920	2°	2280	5	-	-	40	-	-	20	40 + 20	160	154	○
	SGRE2 180	1800	2280	2920	-	70 - 120	950	3°	2360	5	-	-	34	-	-	16	32 + 16	160	154	○
	SGRE2 200	2000	2480	3120	-	70 - 120	980	3°	2360	5	-	-	38	-	-	18	36 + 18	160	154	○
	SGRE2 220	2200	2680	3320	-	70 - 200	1010	3°	2360	5	-	-	40	-	-	20	40 + 20	160	154	○
	SGRE2 250	2500	2980	3620	-	80 - 200	1130	3°	2360	5	-	-	48	-	-	22	44 + 22	160	154	○

● Standard ○ Optional - Non disponibile, nicht verfügbar, not available, pas disponible