






















Cat.	Mod.																					
		Lavoro mm	Ingombro mm	HP min - max	Kg	Giri rotore 540°	Giri rotore 1000°	Categoria 3° punto	931060003	931040001	931990001	931040004	931990002	Mod. TDF	Doppia trasmissione	Doppio rotore	Diametro del rotore	Diametro del rullo	Ruote standard	Ruote opzionali	Kit tabella stradale	Carrello stradale
TSL	TSL 130	1300	1460	30-120	440	1800	-	1°	-	28	14	-	-	-	-	-	170	194	155 / 70 R13	-	○	-
	TSL 140	1400	1560	30-120	480	1800	-	1°	-	28	14	-	-	-	-	-	170	194	155 / 70 R13	-	○	-
	TSL 160	1600	1760	35-120	520	1800	-	1° / 2°	-	32	16	-	-	-	-	-	170	194	155 / 70 R13	-	○	-
	TSL 180	1800	1960	40-120	580	1875	-	1° / 2°	-	36	18	-	-	-	-	-	170	194	155 / 70 R13	-	○	-
	TSL 200	2000	2160	40-120	640	1875	-	1° / 2°	-	40	20	-	-	-	-	-	170	194	155 / 70 R13	-	○	-
	TSL 220	2200	2360	50-120	660	1875	-	1° / 2°	-	44	22	-	-	-	-	-	170	194	155 / 70 R13	-	○	-
	TSL 230	2300	2460	50-120	690	1875	-	1° / 2°	-	48	24	-	-	-	-	-	170	194	155 / 70 R13	-	○	-
	TSL 250	2500	2660	60-120	750	1875	-	1° / 2°	-	56	28	-	-	-	-	-	170	194	155 / 70 R13	-	○	-






















TST	TST 130	1300	1460	40-120	640	1875	1800	1°	16	28	14	28	16	-	-	-	220	220	155 / 70 R13	-	○	-
	TST 140	1400	1560	40-120	650	1875	1800	1°	18	32	16	32	18	-	-	-	220	220	155 / 70 R13	-	○	-
	TST 160	1600	1760	40-120	670	1875	1800	1° / 2°	20	36	18	36	20	-	-	-	220	220	155 / 70 R13	-	○	-
	TST 180	1800	1960	45-120	700	1875	1800	1° / 2°	22	40	20	40	22	-	-	-	220	220	155 / 70 R13	-	○	-
	TST 200	2000	2160	50-120	740	1875	1800	1° / 2°	26	48	24	48	26	-	-	-	220	220	155 / 70 R13	205 / 70 R15	○	-
	TST 220	2200	2360	60-180	790	1875	1800	1° / 2°	28	52	26	52	28	-	-	-	220	220	155 / 70 R13	205 / 70 R15	○	-
	TST 230	2300	2460	60-180	880	1875	1800	1° / 2°	30	56	28	56	30	-	-	-	220	220	155 / 70 R13	205 / 70 R15	○	-
	TST 250	2500	2660	60-180	950	1875	1800	1° / 2°	32	60	30	60	32	-	-	-	220	220	155 / 70 R13	205 / 70 R15	○	-
	TST 280	2800	2985	70-180	1200	1875	1800	2°	36	68	34	68	36	-	-	-	273	273	205 / 70 R15	10.0 / 75 R13,5	○	-
	TST 300	3000	3185	80-180	1300	1875	1800	2°	40	72	36	72	40	-	-	-	273	273	205 / 70 R15	10.0 / 75 R13,5	○	-

TST DT - TST DTDR	TST 250 DT	2500	2780	60-220	1300	1890	1780	2°	32	60	30	60	32	-	●	-	273	273	205 / 70 R15	10.0 / 75 R13,5	○	-
	TST 280 DT	2800	3080	70-220	1450	1890	1780	2°	36	68	34	68	36	-	●	-	273	273	205 / 70 R15	10.0 / 75 R13,5	○	-
	TST 300 DT	3000	3280	80-220	1550	1890	1780	2°	40	72	36	72	40	-	●	-	273	273	205 / 70 R15	10.0 / 75 R13,5	○	-
	TST 320 DT	3200	3480	80-220	1650	1890	1780	2°	44	80	40	80	44	-	●	-	273	273	205 / 70 R15	10.0 / 75 R13,5	○	○
	TST 380 DT	3800	4080	100-220	1700	1500	1440	2°	50	96	48	96	50	-	●	-	323	273	205 / 70 R15	10.0 / 75 R13,5	○	○
	TST 320 DTDR	3200	3480	90-220	1800	1500	1440	2°	40	72	36	72	40	-	●	●	273	273	205 / 70 R15	10.0 / 75 R13,5	○	○
	TST 400 DTDR	4000	4280	120-220	1900	1500	1440	2°	52	96	48	96	52	-	●	●	273	273	205 / 70 R15	10.0 / 75 R13,5	○	○

TST Plus	TST 250 PLUS	2500	2780	100-220	1650	1890	1780	2°	32	64	-	-	32	-	●	-	273	273	205 / 70 R15	10.0 / 75 R13,5	○	-
	TST 280 PLUS	2800	3080	120-220	1750	1890	1780	2°	36	72	-	-	36	-	●	-	273	273	205 / 70 R15	10.0 / 75 R13,5	○	-
	TST 300 PLUS	3000	3280	120-220	1850	1890	1780	2°	40	80	-	-	40	-	●	-	273	273	205 / 70 R15	10.0 / 75 R13,5	○	-
	TST 320 PLUS	3200	3480	130-220	1950	1890	1780	2°	44	88	-	-	44	-	●	-	273	273	205 / 70 R15	10.0 / 75 R13,5	○	○

● Standard ○ Optional - Non disponibile, nicht verfügbar, not available, pas disponible

* = Ruote anteriori
Front wheels
Fronträder
Roues avant

Cat.	Mod.	 Lavoro	 Ingombro	 HP min - max	 Kg	 540° Giri rotore	 1000° Giri rotore	 Categoria 3° punto	 931060003	 931040001	 931990001	 931990002	 Coltelli sagomati	 Mod. TDF	 Doppia trasmissione	 X2 Doppio rotore	 Diametro del rotore	 Diametro del rullo	 Ruote standard	 Ruote opzionali	 Kit tabella stradale	 Carrello stradale
TDF	TDF 200	2000	2195	120-250	1400	-	1800	2°	-	-	-	-	-	52 + 26	-	-	273	273	-	-	○	-
	TDF 230	2300	2495	120-250	1550	-	1800	2°	-	-	-	-	-	60 + 30	-	-	273	273	-	-	○	-
	TDF 250	2500	2695	150-250	1600	-	1800	2°	-	-	-	-	-	64 + 32	-	-	273	273	-	-	○	-
	TDF 280	2800	2995	150-250	1750	-	1800	2°	-	-	-	-	-	72 + 36	-	-	273	273	-	-	○	-
	TDF 300	3000	3195	150-250	1880	-	1800	2°	-	-	-	-	-	80 + 40	-	-	273	273	-	-	○	-

TDF DT TDF DTDR	TDF 230 DT	2300	2630	130-250	1750	-	1780	2°	-	-	-	-	-	60 + 30	●	-	273	273	-	-	○	-
	TDF 250 DT	2500	2830	130-250	1800	-	1780	2°	-	-	-	-	-	64 + 32	●	-	273	273	-	-	○	-
	TDF 280 DT	2800	3130	150-250	1950	-	1780	2°	-	-	-	-	-	72 + 36	●	-	273	273	-	-	○	-
	TDF 300 DT	3000	3330	150-250	2080	-	1780	2°	-	-	-	-	-	80 + 40	●	-	273	273	-	-	○	-
	TDF 320 DT	3200	3500	170-270	2210	-	1780	2°	-	-	-	-	-	84 + 42	●	-	273	273	-	-	○	-
	TDF 380 DT	3800	4130	170-270	2430	-	1780	2°	-	-	-	-	-	100 + 50	●	-	323	273	-	-	○	-
	TDF 320 DTDR	3200	3500	170-270	2250	-	1780	2°	-	-	-	-	-	80 + 40	●	●	273	273	-	-	○	-
	TDF 400 DTDR	4000	4330	170-270	2500	-	1780	2°	-	-	-	-	-	104 + 52	●	●	273	273	-	-	○	-

TFC	TFC 140	1400	1560	30-120	610	1875	-	2°	18	28	14	18	-	-	-	-	170	-	155 / 70 R13	16x6,5/8*	○	-
	TFC 150	1500	1660	30-120	630	1875	-	2°	20	30	15	20	-	-	-	-	170	-	155 / 70 R13	16x6,5/8*	○	-
	TFC 160	1600	1760	40-120	660	1875	-	2°	20	32	16	20	-	-	-	-	170	-	155 / 70 R13	16x6,5/8*	○	-
	TFC 200	2000	2160	40-120	700	1875	-	2°	24	40	20	26	-	-	-	-	170	-	155 / 70 R13	16x6,5/8*	○	-
	TFC 230	2300	2460	50-120	730	1875	-	2°	28	48	24	30	-	-	-	-	170	-	155 / 70 R13	16x6,5/8*	○	-

TFP	TFP 160	1600	1760	40-120	670	1875	-	2°	-	-	-	-	20 **	-	-	-	170	-	155 / 70 R13	16x6,5/8*	○	-
	TFP 190	1900	2060	50-120	700	1875	-	2°	-	-	-	-	26 **	-	-	-	170	-	155 / 70 R13	16x6,5/8*	○	-
	TFP 310	3100	3100	60-150	1300	1875	-	2°	-	-	-	-	42 **	-	-	-	170	-	155 / 70 R13	16x6,5/8*	○	-

* = Ruote anteriori
Front wheels
Fronträder
Roues avant

** = Coppie di supportini
Pair of lugs
Paar Träger
Pair de supports

● Standard ○ Optional - Non disponibile, nicht verfügbar, not available, pas disponible