



















Cat.	Mod.			HP  min - max		1000'  Giri rotore	 Categoria 3° punto						 Diretto Cardano diretto	 Diretto Cardano a frizione	 Diametro del rotore	 Diametro del rullo	 Ruote standard	 Ruote opzionali	 Kit tabelle stradali
TSL-V	TSL-V-15 320	3200	3500	80 - 180	1700	1700	2°	40	64	32	-	40	●	○	170	194	205 / 70 R15	-	●
	TSL-V-15 400	4000	4300	100 - 180	1900	1700	2°	48	80	40	-	48	●	○	170	194	205 / 70 R15	-	●
	TSL-V-15 460	4600	4900	100 - 180	2000	1700	2°	56	96	48	-	56	●	○	170	194	205 / 70 R15	-	●

TST-V	TST-V-15 320	3200	3500	100 - 180	2000	1720	2°	40	72	36	72	40	●	○	220	220	205 / 70 R15	-	●
	TST-V-15 400	4000	4300	110 - 180	2200	1720	2°	52	96	48	96	52	●	○	220	220	205 / 70 R15	-	●
	TST-V-20 320	3200	3500	100 - 280	2050	1720	2° / 3°	40	72	36	72	40	●	○	220	220	205 / 70 R15	10.0 / 75 R13.5	●
	TST-V-20 400	4000	4300	110 - 280	2250	1720	2° / 3°	52	96	48	96	52	●	○	220	220	205 / 70 R15	10.0 / 75 R13.5	●
	TST-V-20 460	4600	4900	120 - 280	2400	1720	2° / 3°	60	112	56	112	60	●	○	220	273	205 / 70 R15	10.0 / 75 R13.5	●
	TST-V-20 500	5000	5300	130 - 280	2800	1720	2° / 3°	64	120	60	120	64	-	●	273	273	205 / 70 R15	10.0 / 75 R13.5	●
	TST-V-25 600	6000	6320	150 - 320	3300	1720	3°	40	144	72	144	40	-	●	273	273	205 / 70 R15	10.0 / 75 R13.5	●
	TST-V-25 640	6400	6720	160 - 320	3600	1720	3°	88	160	80	160	88	-	●	273	273	205 / 70 R15	10.0 / 75 R13.5	●

● Standard ○ Optional - Non disponibile, nicht verfügbar, not available, pas disponible