

























Cat.	Mod.	N° 	 mm	 Profondità lavoro mm	 mm	 mm	 HP min - max	 Categoria 3° punto	 Senza rulli	 2 Rulli	 mm	 mm	 Kit tabelle stradali
DIG 780	DIG 700 / 3	3	700	420	620	1500	60 - 130	2°	480	680	-	-	○
	DIG 780 / 5S	5	780	500	485	2300	80 - 180	2°	690	1040	-	-	○
	DIG 780 / 5	7	780	500	535	2500	80 - 180	2°	720	1100	-	-	○
	DIG 780 / 7	5	780	500	355	2500	100 - 180	2°	930	1310	-	-	○
RIP 780	RIP 700 / 3	3	700	420	620	1500	60 - 130	2°	510	710	-	-	○
	RIP 780 / 5S	5	780	500	485	2300	80 - 180	2°	750	1100	-	-	○
	RIP 780 / 5	5	780	500	535	2500	80 - 180	2°	780	1160	-	-	○
	RIP 780 / 7	7	780	500	355	2500	100 - 180	2°	1020	1400	-	-	○
DIG 950	DIG 950 / 5	5	950	650	535	2500	100 - 200	3°	1225	1525	-	-	○
	DIG 950 / 7S	7	950	650	355	2500	130 - 200	3°	1445	1695	-	-	○
	DIG 950 / 7	7	950	650	430	3000	130 - 250	3°	1545	1895	-	-	○
	DIG 950 / 9	9	950	650	390	3500	150 - 300	3°	1715	2115	-	-	○
RIP 950	RIP 950 / 5	5	950	650	535	2500	100 - 200	3°	1300	1600	-	-	○
	RIP 950 / 7S	7	950	650	355	2500	130 - 200	3°	1550	1800	-	-	○
	RIP 950 / 7	7	950	650	430	3000	130 - 250	3°	1650	2000	-	-	○
	RIP 950 / 9	9	950	650	390	3500	150 - 300	3°	1850	2250	-	-	○
RIP 1050	RIP 1050 / 5	5	1050	750	535	2500	150 - 250	3°	1920	2400	-	-	○
	RIP 1050 / 7	7	1050	750	430	3000	180 - 280	3°	2050	2600	-	-	○
	RIP 1050 / 9	9	1050	750	450	4000	280 - 400	3°	2300	3000	-	-	○
RIP 1350	RIP 1350 / 1	-	1350	1000	-	-	120 - 250	3°	-	-	350	500	○
	RIP 1350 / 2	-	1350	1000	-	-	150 - 300	3°	-	-	2000	1120	○
	RIP 1350 / 3	-	1350	1000	-	-	200 - 500	3°	-	-	2000	1300	○
KRW	KRW 100 / 2	2	450	200	-	740 - 1210	50 - 90	2°	160	-	-	-	-
	KRW 140 / 4	4	450	200	-	1400 - 1650	60 - 90	2°	210	-	-	-	-
	KRW 180 / 4	4	450	200	-	1850 - 1150	70 - 90	2°	230	-	-	-	-
	KRW 200 / 6	6	450	200	-	2050 - 2250	80 - 120	2°	240	-	-	-	-
	KRW 240 / 6	6	450	200	-	2150 - 2500	100 - 120	2°	260	-	-	-	-
KRC	KRC 300 / 6	6	920	500	500	3000	130 - 280	3°	960	-	-	-	-
	KRC 350 / 6	6	920	500	640	3500	130 - 300	3°	1010	-	-	-	-
	KRC 400 / 8	8	920	500	500	4000	160 - 350	3°	1330	-	-	-	-
KRS	KRS 300 / 6	6	970	550	500	3000	130 - 280	3°	950	-	-	-	-
	KRS 350 / 6	6	970	550	640	3500	130 - 300	3°	1030	-	-	-	-
	KRS 400 / 8	8	970	550	500	4000	160 - 350	3°	1360	-	-	-	-

Cat.	Mod.	N° 	 mm	 Profondità lavoro mm	 mm	 mm	 HP min - max	 Categoria 3° punto	 Senza rulli	 2 Rulli	 mm	 mm	 Kit tabelle stradali
KVB	KVB 300	7	980	750	605	3000	180 - 280	3°	1500	-	-	-	-
	KVB 400	9	980	750	605	4000	280 - 400	3°	2000	-	-	-	-
KRS	KRS 300 / 6	7	980	750	605	3000	180 - 280	3°	1500	-	-	-	-
	KRS 400 / 8	9	980	750	605	4000	280 - 400	3°	2000	-	-	-	-