


















| Cat.  | Mod.      |  Lavoro |  Ingombro |  HP<br>min - max |  Kg |  Categoria<br>3° punto |  Giri rotore<br>540° |  Numero<br>cinghie |  |  |  |  |  |  |  |  Diametro<br>del rotore |  Diametro<br>del rullo |  Kit tabella<br>stradali |
|-------|-----------|--|--|---|--|---|---|---|---|---|---|---|---|---|---|--|---|---|
| DSK   | DSK 120   | 1200   | 1340   | 30 - 80   | 380  | 2°  | 2590  | 3   | 14  | 40  | 20  | -   | -   | -   | -   | 130  | 114   | ○   |
|       | DSK 140   | 1400   | 1540   | 30 - 80   | 410  | 2°  | 2590  | 3   | 16  | 48  | 24  | -   | -   | -   | -   | 130  | 114   | ○   |
|       | DSK 160   | 1600   | 1740   | 35 - 80   | 450  | 2°  | 2590  | 4   | 18  | 56  | 28  | -   | -   | -   | -   | 130  | 114   | ○   |
|       | DSK 180   | 1800   | 1940   | 40 - 80   | 480  | 2°  | 2590  | 4   | 20  | 60  | 30  | -   | -   | -   | -   | 130  | 114   | ○   |
| DSKE  | DSKE 120  | 1200   | 1550   | 30 - 80   | 400  | 2°  | 2590  | 3   | 14  | 40  | 20  | -   | -   | -   | -   | 130  | 114   | ○   |
|       | DSKE 140  | 1400   | 1750   | 30 - 80   | 430  | 2°  | 2590  | 3   | 16  | 48  | 24  | -   | -   | -   | -   | 130  | 114   | ○   |
|       | DSKE 160  | 1600   | 1950   | 35 - 80   | 470  | 2°  | 2590  | 4   | 18  | 56  | 28  | -   | -   | -   | -   | 130  | 114   | ○   |
|       | DSKE 180  | 1800   | 2150   | 40 - 80   | 500  | 2°  | 2590  | 4   | 20  | 60  | 30  | -   | -   | -   | -   | 130  | 114   | ○   |
| LG2   | LG2 120   | 1200   | 1390   | 35 - 120  | 570  | 2°  | 2280  | 3   | -   | -   | 22  | 10  | 28  | -   | -   | 150  | 154   | ○   |
|       | LG2 140   | 1400   | 1590   | 40 - 120  | 590  | 2°  | 2280  | 3   | -   | -   | 26  | 12  | 32  | -   | -   | 150  | 154   | ○   |
|       | LG2 160   | 1600   | 1790   | 40 - 120  | 610  | 2°  | 2280  | 4   | -   | -   | 30  | 14  | 36  | -   | -   | 150  | 154   | ○   |
|       | LG2 180   | 1800   | 1990   | 50 - 120  | 640  | 2°  | 2280  | 4   | -   | -   | 34  | 16  | 40  | -   | -   | 150  | 154   | ○   |
|       | LG2 200   | 2000   | 2190   | 50 - 120  | 700  | 2°  | 2280  | 4   | -   | -   | 38  | 18  | 44  | -   | -   | 150  | 154   | ○   |
| LGE2  | LGE2 120  | 1200   | 1620   | 35 - 120  | 590  | 2°  | 2280  | 3   | -   | -   | 22  | 10  | 28  | -   | -   | 150  | 154   | ○   |
|       | LGE2 140  | 1400   | 1820   | 40 - 120  | 610  | 2°  | 2280  | 3   | -   | -   | 26  | 12  | 32  | -   | -   | 150  | 154   | ○   |
|       | LGE2 160  | 1600   | 2020   | 40 - 120  | 630  | 2°  | 2280  | 4   | -   | -   | 30  | 14  | 36  | -   | -   | 150  | 154   | ○   |
|       | LGE2 180  | 1800   | 2220   | 50 - 120  | 660  | 2°  | 2280  | 4   | -   | -   | 34  | 16  | 40  | -   | -   | 150  | 154   | ○   |
|       | LGE2 200  | 2000   | 2420   | 50 - 120  | 720  | 2°  | 2280  | 4   | -   | -   | 38  | 18  | 44  | -   | -   | 150  | 154   | ○   |
| SG2   | SG2 160   | 1600   | 1790   | 50 - 120  | 780  | 2°  | 2280  | 4   | -   | -   | 30  | -   | -   | 14  | 28 + 14   | 160  | 154   | ○   |
|       | SG2 180   | 1800   | 1990   | 50 - 120  | 840  | 2°  | 2280  | 4   | -   | -   | 34  | -   | -   | 16  | 32 + 16   | 160  | 154   | ○   |
|       | SG2 200   | 2000   | 2190   | 60 - 120  | 870  | 2°  | 2280  | 5   | -   | -   | 38  | -   | -   | 18  | 36 + 18   | 160  | 154   | ○   |
|       | SG2 220   | 2200   | 2390   | 60 - 120  | 900  | 2°  | 2280  | 5   | -   | -   | 40  | -   | -   | 20  | 40 + 20   | 160  | 154   | ○   |
| SGR2  | SGR2 220  | 2200   | 2390   | 70 - 200  | 980  | 3°  | 2360  | 5   | -   | -   | 40  | -   | -   | 20  | 40 + 20   | 160  | 154   | ○   |
|       | SGR2 250  | 2500   | 2690   | 80 - 200  | 1100   | 3°  | 2360  | 5   | -   | -   | 48  | -   | -   | 22  | 44 + 22   | 160  | 154   | ○   |
| SGE2  | SGE2 160  | 1600   | 2080   | 50 - 120  | 800  | 2°  | 2280  | 4   | -   | -   | 30  | -   | -   | 14  | 28 + 14   | 160  | 154   | ○   |
|       | SGE2 180  | 1800   | 2280   | 50 - 120  | 860  | 2°  | 2280  | 4   | -   | -   | 34  | -   | -   | 16  | 32 + 16   | 160  | 154   | ○   |
|       | SGE2 200  | 2000   | 2480   | 60 - 120  | 890  | 2°  | 2280  | 5   | -   | -   | 38  | -   | -   | 18  | 36 + 18   | 160  | 154   | ○   |
|       | SGE2 220  | 2200   | 2680   | 60 - 120  | 920  | 2°  | 2280  | 5   | -   | -   | 40  | -   | -   | 20  | 40 + 20   | 160  | 154   | ○   |
| SGRE2 | SGRE2 180 | 1800   | 2280   | 70 - 120  | 950  | 3°  | 2360  | 5   | -   | -   | 34  | -   | -   | 16  | 32 + 16   | 160  | 154   | ○   |
|       | SGRE2 200 | 2000   | 2480   | 70 - 120  | 980  | 3°  | 2360  | 5   | -   | -   | 38  | -   | -   | 18  | 36 + 18   | 160  | 154   | ○   |
|       | SGRE2 220 | 2200   | 2680   | 70 - 200  | 1010   | 3°  | 2360  | 5   | -   | -   | 40  | -   | -   | 20  | 40 + 20   | 160  | 154   | ○   |
|       | SGRE2 250 | 2500   | 2980   | 80 - 200  | 1130   | 3°  | 2360  | 5   | -   | -   | 48  | -   | -   | 22  | 44 + 22   | 160  | 154   | ○   |