

CLS 250 - 400



Standard Equipment


- 3 points ISO universal front hitch with 3rd category fork
- Bolted shank holder
- Hydraulic rear roller adjustment
- Rear leveling bar with adjustable deflectors
- Shank with wings and double spring non-stop safety
- EC guard kit

VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale
Via dell'Industria, 27/A
36045 Alonte (VI) - ITALY
Tel. +39 0444 436247
Fax +39 0444 436237
www.vigolo.com - info@vigolo.com



Ancore con alette e sicurezza non-stop a doppia molla (CLS)
 Dents à ailettes et sécurité à double ressort non-stop (CLS)
 Shank with wings and double spring non-stop safety (CLS)
 Zinken mit Flügel und Doppelfeder Non-Stop-Sicherheit (CLS)

Mod.	N°	 Profondità lavoro mm	 mm	 mm Lavoro	 mm Ingombro	HP  min - max	 kg Rullo Export	 kg Rullo Packer Ø 323 / 470	 kg Anelli D. 600	 kg Tandem
CLS 250	8	5-35	280	2500	2500	130-250	2000	2300	2100	2250
CLS 300	10	5-35	280	3000	3000	150-250	2100	2400	2200	2350
CLS 350	12	5-35	280	3500	3500	160-250	2200	2600	2300	2450
CLS 400	14	5-35	280	4000	4000	170-250	2400	2900	2500	2650

VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale
 Via dell'Industria, 27/A
 36045 Alonte (VI) - ITALY
 Tel. +39 0444 436247
 Fax +39 0444 436237
www.vigolo.com - info@vigolo.com