

DB 300 - 450



Standard Equipment


- 3 points ISO universal hitch with 2nd category oscillating fork (pins of 2nd/3rd cat)
- One speed central gearbox 540' eco/1000' mod. Vigolo G8, 2 pto
- Double body transmission structure with increased height
- Transmission body by case-hardened and hardened gears
- Endplates with height-adjustable shock absorber
- Rear levelling blade
- Lateral rear roller adjustment by pins
- Side stiffening braces
- Arrangement for seeder coupler (ASM and ASI N)
- Arrangement for quick-changing tines
- Cardan shaft with disk clutch (tractor side fork 1" 3/8 Z6)
- EC guard kit

VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale
Via dell'Industria, 27/A
36045 Alonte (VI) - ITALY
Tel. +39 0444 436247
Fax +39 0444 436237
www.vigolo.com - info@vigolo.com

Misure coltelli
Abmessungen Messer
Knives measures
Mesures couteaux

A	330	mm
B	110	mm
C	15	mm
D	66	mm
E Ø	16,5	mm



240

Cuscinetti conici a rulli a bagno d'olio
Oil-immersed Tapered roller bearings
Ölbad Kegelrollerlager
Roulements coniques à bain d'huile



Mod.	Lavoro		HP min - max	N°	540'		540' ECO	540' - 1000'	Rullo Export	Rullo Spuntoni Rullo Spirale	Rullo Packer Ø 323 / 470	Rullo Packer Ø 355 / 500	Rullo Packer Ø 406 / 550
	Lavoro	Ingombro			540'	1000'							
DB 300	2980	2995	110-250	12	-	395	-	280 - 510	1400	1510	-	1650	1700
DB 350	3460	3500	120-250	14	-	395	-	280 - 510	1550	1750	-	1940	2000
DB 400	4005	4055	130-250	16	-	395	-	280 - 510	1800	1950	-	2140	2210
DB 450	4485	4535	140-250	18	-	395	-	280 - 510	2000	2100	-	2500	2650

VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale
Via dell'Industria, 27/A
36045 Alonte (VI) - ITALY
Tel. +39 0444 436247
Fax +39 0444 436237
www.vigolo.com - info@vigolo.com