

## EN-L 165 - 250



### Standard Equipment

- 3 points ISO universal hitch with 2nd category oscillating fork
- One speed central gearbox 540'/540' eco mod. Vigolo A8, 1 pto
- Endplates with height-adjustable shock absorber
- Rear levelling blade
- Lateral rear roller adjustment by pins
- Arrangement for electric seeder (EN-SKEL) and seeder coupler (ASM)
- Cardan shaft with disk clutch (tractor side fork 1" 3/8 Z6) - EC guard kit


---

### VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale  
Via dell'Industria, 27/A  
36045 Alonte (VI) - ITALY  
Tel. +39 0444 436247  
Fax +39 0444 436237  
[www.vigolo.com](http://www.vigolo.com) - [info@vigolo.com](mailto:info@vigolo.com)

**Misure coltelli**  
**Abmessungen Messer**  
**Knives measures**  
**Mesures couteaux**











A	280	mm
B	90	mm
C	12	mm
D	50	mm
E Ø	16,5	mm



215

Cuscinetti a sfera a bagno d'olio  
 Oil-immersed ball bearings  
 Ölbad Kugellager  
 Roulements à billes à bain d'huile



Mod.	 Lavoro	 Ingombro	 HP min - max	 N°	 540'	 540' ECO	 540' - 1000'	 Rullo Export kg	 Rullo Spuntoni Rullo Spirale kg	 Rullo Packer Ø 323 / 470 kg
EN-L 165	1625	1675	30 - 90	7	340	472	280 - 510	550	545	660
EN-L 185	1840	1890	40 - 90	8	340	472	280 - 510	605	595	725
EN-L 200	2055	2105	40 - 120	9	340	472	280 - 510	660	690	790
EN-L 225	2270	2320	40 - 120	10	340	472	280 - 510	715	765	855
EN-L 250	2510	2545	50 - 120	11	340	472	280 - 510	770	840	920

**VIGOLO Srl Unipersonale**

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale  
 Via dell'Industria, 27/A  
 36045 Alonte (VI) - ITALY  
 Tel. +39 0444 436247  
 Fax +39 0444 436237  
 www.vigolo.com - info@vigolo.com