

EN-T 095 - 185



Standard Equipment


- 3 points ISO universal hitch with 1st category fork (adjustable width, pins 1st/2nd cat.)
- One speed central gearbox 540'/540' eco mod. Vigolo A6, 1 pto
- Endplates with height-adjustable shock absorber
- Rear levelling blade
- Lateral rear roller adjustment by pins
- Arrangement for electric seeder (EN-SKEL)
- Cardan shaft with disk clutch (tractor side fork 1" 3/8 Z6)
- EC guard kit

VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale
Via dell'Industria, 27/A
36045 Alonte (VI) - ITALY
Tel. +39 0444 436247
Fax +39 0444 436237
www.vigolo.com - info@vigolo.com

Misure coltelli
Abmessungen Messer
Knives measures
Mesures couteaux











A	280	mm
B	90	mm
C	12	mm
D	50	mm
E Ø	16,5	mm



215

Cuscinetti a sfera a bagno d'olio
Oil-immersed ball bearings
Ölbad Kugellager
Roulements à billes à bain d'huile



Mod.	 Lavoro	 Ingombro	 HP min - max	 N°	 540'	 540' ECO	 540' - 1000'	 kg Rullo Export	 kg Rullo Spuntoni Rullo Spirale	 kg Rullo Packer Ø 323 / 470
EN-T 095	980	1030	25 - 90	4	280	389	280 - 510	390	410	460
EN-T 120	1195	1245	25 - 90	5	280	389	280 - 510	425	440	500
EN-T 145	1410	1460	30 - 90	6	280	389	280 - 510	460	480	580
EN-T 165	1625	1675	30 - 90	7	280	389	280 - 510	520	540	620
EN-T 185	1840	1890	40 - 90	8	280	389	280 - 510	570	595	700

VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale
Via dell'Industria, 27/A
36045 Alonte (VI) - ITALY
Tel. +39 0444 436247
Fax +39 0444 436237
www.vigolo.com - info@vigolo.com