

ER 300 - 400



Standard Equipment


- 3 points ISO universal hitch with 2nd category oscillating fork (pins of 2nd/3rd cat)
- One speed central gearbox 540'/540' eco mod. Vigolo A8, 2 pto
- Transmission body by case-hardened and hardened gears
- Endplates with height-adjustable shock absorber
- Rear levelling blade
- Lateral rear roller adjustment by pins
- Curved side stiffening braces
- Arrangement for seeder coupler (ASM and ASI N)
- Cardan shaft with disk clutch (tractor side fork 1" 3/8 Z6)
- EC guard kit

VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale
Via dell'Industria, 27/A
36045 Alonte (VI) - ITALY
Tel. +39 0444 436247
Fax +39 0444 436237
www.vigolo.com - info@vigolo.com

Misure coltelli
Abmessungen Messer
Knives measures
Mesures couteaux

A	320	mm
B	90	mm
C	14	mm
D	50	mm
E Ø	16,5	mm



240

Cuscinetti a sfera a bagno d'olio
Oil-immersed ball bearings
Ölbad Kugellager
Roulements à billes à bain d'huile



Mod.	 Lavoro	 Ingombro	 N°	 HP min - max	 540'	 540' ECO	 kg Rullo Export	 kg Rullo Spuntoni Rullo Spirale	 kg Rullo Packer Ø 323 / 470	 kg Rullo Packer Ø 355 / 500
ER 300	2980	2995	12	70-140	340	472	995	1040	1170	1250
ER 350	3460	3500	14	90-140	340	472	1160	1210	1380	1580
ER 400	4005	4055	16	100-140	340	472	1330	1400	1610	1710

VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale
Via dell'Industria, 27/A
36045 Alonte (VI) - ITALY
Tel. +39 0444 436247
Fax +39 0444 436237
www.vigolo.com - info@vigolo.com