

FK 095 - 205













Standard Equipment

- 3 points ISO universal hitch with 1st category fork (adjustable width, pins of 1st/2nd cat)
- One speed central gearbox 540'/540' eco mod. Vigolo A6, 1 pto
- Transmission by chain
- 4 curved blades per flange
- Rear hood
- Central rear roller adjustment with handle (only for versions with rear roller)
- Cardan shaft with disk clutch (tractor side fork 1" 3/8 Z6)
- EC guard kit

VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale
Via dell'Industria, 27/A
36045 Alonte (VI) - ITALY
Tel. +39 0444 436247
Fax +39 0444 436237
www.vigolo.com - info@vigolo.com



Mod.	 Lavoro	 Ingombro	 HP min - max	 N° zappe *	 540'	 540' ECO	 kg Slitte	 kg Rullo Export	 kg Rullo Spuntoni Rullo Spirale	 kg Rullo Packer Ø 323 / 470
FK 095	950	1100	25 - 80	20	210	292	265	300	320	370
FK 105	1050	1200	25 - 80	20	210	292	280	320	340	390
FK 125	1250	1400	25 - 80	24	210	292	310	340	360	420
FK 135	1350	1500	30 - 80	28	210	292	330	370	390	470
FK 145	1450	1600	30 - 80	28	210	292	350	400	420	490
FK 165	1650	1800	30 - 80	36	210	292	380	420	440	520
FK 185	1850	2000	40 - 80	40	210	292	400	430	450	570
FK 205	2050	2200	40 - 80	40	210	292	440	480	500	630



VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale
 Via dell'Industria, 27/A
 36045 Alonte (VI) - ITALY
 Tel. +39 0444 436247
 Fax +39 0444 436237
www.vigolo.com - info@vigolo.com