

FM 155 - 225













Standard Equipment

- 3 points ISO universal hitch with 1st/2nd category fork
- One speed central gearbox 540'/540' eco mod. Vigolo B8, 1 pto
- Transmission by chain
- 4 curved blades per flange
- Rear hood
- Lateral rear roller adjustment by pins (only for versions with rear roller)
- Central cardan shaft with disk clutch (tractor side fork 1" 3/8 Z6)
- EC guard kit

VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale
Via dell'Industria, 27/A
36045 Alonte (VI) - ITALY
Tel. +39 0444 436247
Fax +39 0444 436237
www.vigolo.com - info@vigolo.com



Mod.	 Lavoro	 Ingombro	 HP min - max	 N° zappe *	 540' Standard	 540' ECO	 kg Slitte	 kg Rullo Export	 kg Rullo Spuntoni Rullo Spirale	 kg Rullo Packer Ø 323 / 470
FM 155	1550	1750	40 - 120	28	270	375	420	475	495	560
FM 165	1650	1850	45 - 120	28	270	375	440	500	520	600
FM 175	1750	1950	45 - 120	32	270	375	450	520	540	640
FM 185	1850	2050	50 - 120	32	270	375	470	540	560	680
FM 205	2050	2250	55 - 120	36	270	375	500	580	600	730
FM 225	2250	2450	60 - 120	40	270	375	560	550	670	780



VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale
 Via dell'Industria, 27/A
 36045 Alonte (VI) - ITALY
 Tel. +39 0444 436247
 Fax +39 0444 436237
www.vigolo.com - info@vigolo.com