

## FM 155 - 225



### Standard Equipment











- 3 points ISO universal hitch with 1st/2nd category fork
- One speed central gearbox 540'/540' eco mod. Vigolo B8, 1 pto
- Transmission by chain
- 4 curved blades per flange
- Rear hood
- Lateral rear roller adjustment by pins (only for versions with rear roller)
- Central cardan shaft with disk clutch (tractor side fork 1" 3/8 Z6)
- EC guard kit

---

### VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale  
Via dell'Industria, 27/A  
36045 Alonte (VI) - ITALY  
Tel. +39 0444 436247  
Fax +39 0444 436237  
[www.vigolo.com](http://www.vigolo.com) - [info@vigolo.com](mailto:info@vigolo.com)



| Mod.   | <br>Lavoro | <br>Ingombro | <br>HP<br>min - max | <br>N° zappe * | <br>540' Standard | <br>540' ECO | <br>kg<br>Slitte | <br>kg<br>Rullo Export | <br>kg<br>Rullo Spuntoni<br>Rullo Spirale | <br>kg<br>Rullo Packer<br>Ø 323 / 470 |
|--------|---|---|--|---|--|---|---|---|--|--|
| FM 155 | 1550  | 1750  | 40 - 120   | 28  | 270  | 375   | 420   | 475   | 495  | 560  |
| FM 165 | 1650  | 1850  | 45 - 120   | 28  | 270  | 375   | 440   | 500   | 520  | 600  |
| FM 175 | 1750  | 1950  | 45 - 120   | 32  | 270  | 375   | 450   | 520   | 540  | 640  |
| FM 185 | 1850  | 2050  | 50 - 120   | 32  | 270  | 375   | 470   | 540   | 560  | 680  |
| FM 205 | 2050  | 2250  | 55 - 120   | 36  | 270  | 375   | 500   | 580   | 600  | 730  |
| FM 225 | 2250  | 2450  | 60 - 120   | 40  | 270  | 375   | 560   | 550   | 670  | 780  |



## VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale  
 Via dell'Industria, 27/A  
 36045 Alonte (VI) - ITALY  
 Tel. +39 0444 436247  
 Fax +39 0444 436237  
[www.vigolo.com](http://www.vigolo.com) - [info@vigolo.com](mailto:info@vigolo.com)