

LG2 120 - 200



Standard Equipment


- 3 points ISO universal hitch with 2nd category fork
- Gearbox with free wheel 540', mod. Vigolo F810
- Gearbox in internal position of the machine
- Double counter-knife
- Rear roller adjustable in position with scraper or self-cleaning
- Front rounded and flattened side with anti-jamming chains
- Hydraulic cylinder for machine tilting
- Hydraulic cylinder for lateral displacement
- Opening rear door for maintenance
- Direct cardan shaft (tractor side fork 1" 3/8 Z6)
- Front protection flaps
- EC guard kit

VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale
Via dell'Industria, 27/A
36045 Alonte (VI) - ITALY
Tel. +39 0444 436247
Fax +39 0444 436237
www.vigolo.com - info@vigolo.com



Fiancata arrotondata
Rounded side
Abgerundetes Gehäuse
Côté arrondie



Supporto forgiato
Cast lug
Geschmiedeter Träger
Support forgé



Mod.	 Lavoro	 Ingombro	 HP min - max	 Kg	 10	 28	 22	 3
LG2 120	1200	1390	35 - 100	570	10	28	22	3
LG2 140	1400	1590	40 - 100	590	12	32	26	3
LG2 160	1600	1790	40 - 100	610	14	36	30	4
LG2 180	1800	1990	50 - 100	640	16	40	34	4
LG2 200	2000	2190	50 - 100	700	18	44	38	4

VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale
Via dell'Industria, 27/A
36045 Alonte (VI) - ITALY
Tel. +39 0444 436247
Fax +39 0444 436237
www.vigolo.com - info@vigolo.com