

RIP 950











Standard Equipment

- 3 points ISO universal hitch with 3rd category fork
- Height of sub-frame: 950 mm
- Welded shank holder (DIG)
- Bolted shank holder (RIP)
- Shanks with security bolt
- Reversible shares
- Bilateral coulters with double position in height and central soil opening blades
- EC guard kit

VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale
Via dell'Industria, 27/A
36045 Alonte (VI) - ITALY
Tel. +39 0444 436247
Fax +39 0444 436237
www.vigolo.com - info@vigolo.com

| Mod. | N°  |  mm |  Prof. lavoro mm |  mm |  mm | HP  min - max |  kg Senza rulli |  kg 2 Rulli |
|--------------|--|--|---|--|---|--|---|---|
| RIP 950 / 5 | 5 | 950 | 650 | 535 | 2500 | 100 - 200 | 1300 | 1600 |
| RIP 950 / 7S | 7 | 950 | 650 | 355 | 2500 | 130 - 200 | 1550 | 1800 |
| RIP 950 / 7 | 7 | 950 | 650 | 430 | 3000 | 130 - 250 | 1650 | 2000 |
| RIP 950 / 9 | 9 | 950 | 650 | 390 | 3500 | 150 - 300 | 1850 | 2250 |

