

RSA MAX 180 - 320



Standard Equipment

- 3 points ISO universal hitch with 2nd category fork
- Gearbox with free wheel 540', 1 pto, mod. Vigolo L810 (RSA MAX 180÷250)
- Gearbox with free wheel 1000', 1 pto, mod. Vigolo E810 (RSA MAX 280÷320)
- Arrangement for version 540'/1000' with inversion of the pulleys
- Reinforced double frame
- Triple counter-knife
- Hydraulic side shift through double tube of headstock
- Rear roller adjustable in height with scraper, increased bearings
- Front rounded and flattened side
- Opening rear door for maintenance
- Direct cardan shaft (tractor side fork 1" 3/8 Z6)
- Front protection flaps
- EC guard kit


VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale
Via dell'Industria, 27/A
36045 Alonte (VI) - ITALY
Tel. +39 0444 436247
Fax +39 0444 436237
www.vigolo.com - info@vigolo.com

RSA Max 180-300 RSA Max 320



Fiancata arrotondata
Rounded side
Abgerundetes Gehäuse
Côté arrondie



Supporto forgiato
Cast lug
Geschmiedeter Träger
Support forgé



Mod.	 Lavoro mm	 Ingombro mm	 HP min - max	 Kg	 mm	 mm	 mm	 mm
RSA Max 180	1800	1990	40 - 120	790	16	32 + 16	± 250	5
RSA Max 200	2000	2190	50 - 120	840	18	36 + 18	± 250	5
RSA Max 220	2200	2390	50 - 120	910	20	40 + 20	± 250	5
RSA Max 250	2500	2690	60 - 120	980	22	44 + 22	± 250	5
RSA Max 280	2800	2990	70 - 180	1050	24	48 + 24	± 250	6
RSA Max 300	3000	3190	80 - 180	1120	28	56 + 28	± 250	6
RSA Max 320	3200	3390	80 - 180	1150	32	64 + 32	± 250	6

VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale
Via dell'Industria, 27/A
36045 Alonte (VI) - ITALY
Tel. +39 0444 436247
Fax +39 0444 436237
www.vigolo.com - info@vigolo.com