

TDF 200 - 300





Standard Equipment

- 3 points ISO universal hitch with 2nd category fork
- Gearbox with free wheel 1000', 1 pto, mod. Vigolo E810
- Arrangement for version 540' with inversion of the pulleys
- Adjustable and shaped counter-knife
- Frame with increased thickness with screwed hood liner
- Manual side shift through double tube of headstock
- Rear roller adjustable in height with scraper
- Opening rear door for maintenance
- Direct cardan shaft (tractor side fork 1" 3/8 Z6)
- Side protection blades
- Front protection chains
- EC guard kit

VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale
Via dell'Industria, 27/A
36045 Alonte (VI) - ITALY
Tel. +39 0444 436247
Fax +39 0444 436237
www.vigolo.com - info@vigolo.com



Mod.	 Lavoro	 Ingombro	 min - max			 mm	
TDF 200	2000	2195	120-250	1300	52 + 26	± 200	6
TDF 230	2300	2495	120-250	1490	60 + 30	± 200	6
TDF 250	2500	2695	150-250	1570	64 + 32	± 200	6
TDF 280	2800	2995	150-250	1740	72 + 36	± 200	6
TDF 300	3000	3195	250-250	1880	80 + 40	± 200	6



VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale
 Via dell'Industria, 27/A
 36045 Alonte (VI) - ITALY
 Tel. +39 0444 436247
 Fax +39 0444 436237
www.vigolo.com - info@vigolo.com