

## TK2/R 100 - 200




### Standard Equipment

- 3 points ISO universal hitch with 1st category fork, 2nd category pins for front use, double headstock for front and rear use
- Gearbox with free wheel 1000', 2 pto
- Hydraulic side shift
- Rear roller adjustable in position with scraper or self-cleaning
- Closed shredding chamber with increased volume for material internal discharge
- Direct cardan shaft (tractor side fork 1" 3/8 Z6)
- Front protection flaps
- EC guard kit

---










### VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale  
Via dell'Industria, 27/A  
36045 Alonte (VI) - ITALY  
Tel. +39 0444 436247  
Fax +39 0444 436237  
[www.vigolo.com](http://www.vigolo.com) - [info@vigolo.com](mailto:info@vigolo.com)



Supporto sagomato  
Shaped lug  
Profilerter Träger  
Support profilé



Mod.	 Lavoro mm	 Ingombro mm	HP  min - max	 Kg				 ± 125	 2
TK2/R 100	1000	1125	25-80	270	12	32	16	± 125	2
TK2/R 120	1200	1325	25-80	280	14	40	20	± 125	2
TK2/R 140	1400	1525	30-80	310	16	48	24	± 125	3
TK2/R 150	1500	1625	30-80	330	16	52	26	± 125	3
TK2/R 160	1600	1725	30-80	350	18	56	28	± 125	3
TK2/R 180	1800	1925	40-80	380	20	60	30	± 125	4
TK2/R 200	2000	2125	40-80	410	22	64	32	± 125	4

## VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale  
Via dell'Industria, 27/A  
36045 Alonte (VI) - ITALY  
Tel. +39 0444 436247  
Fax +39 0444 436237  
[www.vigolo.com](http://www.vigolo.com) - [info@vigolo.com](mailto:info@vigolo.com)