

VDB 600 - 800



Standard Equipment


- 3 points ISO universal hitch with 3rd category oscillating fork
- Transmission with one speed lateral gearboxes 1000' mod. Vigolo G8 and Increased central gearbox
- Double body transmission structure with increased height
- Transmission body by case-hardened and hardened gears
- Endplates with height-adjustable shock absorber for soil adaptation
- Adjustable rear levelling blade mounted on rear roller
- Lateral rear roller adjustment by pins
- Locking safety system in closed position with automatic sequential release
- Arrangement for floating system
- Arrangement for quick-changing tines
- Central direct cardan shaft PLUS 500 hp (tractor side fork 1" 3/4 Z20)
- Side cardanshafts with automatic torque clutch PLUS 500 hp
- Rear light kit with road travel tables kit
- EC guard kit

VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale
Via dell'Industria, 27/A
36045 Alonte (VI) - ITALY
Tel. +39 0444 436247
Fax +39 0444 436237
www.vigolo.com - info@vigolo.com

Misure coltelli
Abmessungen Messer
Knives measures
Mesures couteaux

A	330	mm
B	110	mm
C	15	mm
D	66	mm
E Ø	16,5	mm




240

Cuscinetti conici a rulli a bagno d'olio
Oil-immersed Tapered roller bearings
Ölbad Kegelrollerlager
Roulements coniques à bain d'huile



Mod.	Lavoro	Ingombro	HP min - max	N°	1000'	1000'	Rullo Export	Rullo Spuntoni Rullo Spirale	Rullo Packer Ø 323 / 470	Rullo Packer Ø 355 / 500	Rullo Packer Ø 406 / 550
VDB-30 600	5990	6030	200-500	24	395	-	3900	4100	-	4500	4750
VDB-30 700	6950	6980	220-500	28	395	-	4250	4450	-	4920	5100
VDB-30 750	7430	7460	250-500	30	395	-	4400	4630	-	5000	5200
VDB-30 800	7910	7940	250-500	32	395	-	4600	4850	-	5100	5320



VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale
Via dell'Industria, 27/A
36045 Alonte (VI) - ITALY
Tel. +39 0444 436247
Fax +39 0444 436237
www.vigolo.com - info@vigolo.com