

VPX 410 - 620



Standard Equipment


- 3 points ISO universal reinforced hitch with 2nd/3rd category oscillating fork
- Transmission with one speed lateral gearboxes 1000' mod. Vigolo G7
- Double body transmission structure
- Transmission body by case-hardened and hardened gears
- Endplates with height-adjustable shock absorber
- Rear levelling blade mounted on rear roller
- Lateral rear roller adjustment by pins
- Locking safety system in closed position with automatic sequential release
- Arrangement for floating system
- Central cardan shaft with disk clutch (tractor side fork 1" 3/8 Z6)
- Shear-bolt protected side cardan shafts
- Rear light kit with road travel tables kit
- EC guard kit

VIGOLO Srl Unipersonale

Dir. e Coord. di Vigolo Flavio Holding Srl Unipersonale
Via dell'Industria, 27/A
36045 Alonte (VI) - ITALY
Tel. +39 0444 436247
Fax +39 0444 436237
www.vigolo.com - info@vigolo.com

Misure coltelli
Abmessungen Messer
Knives measures
Mesures couteaux












A	320	mm
B	90	mm
C	14	mm
D	50	mm
E Ø	16,5	mm



215

Cuscinetti conici a rulli a bagno d'olio
Oil-immersed Tapered roller bearings
Ölbad Kegelelager
Roulements coniques à bain d'huile



Mod.	 Lavoro	 Ingombro	 HP min - max	 N°	 1000'	 1000'	 kg Rullo Export	 kg Rullo Spuntoni Rullo Spirale	 kg Rullo Packer Ø 323 / 470	 kg Rullo Packer Ø 355 / 500	 kg Rullo Packer Ø 406 / 550
VPX-20 410	4100	4190	120-320	18	395	280 - 510	2380	2500	2640	2710	2870
VPX-20 460	4530	4620	120-320	20	395	280 - 510	2635	2765	2900	2990	3160
VPX-20 500	4960	5050	130-320	22	395	280 - 510	2760	2920	3040	3150	3330
VPX-25 540	5400	5485	140-380	24	395	280 - 510	2930	3120	-	3450	3640
VPX-25 580	5830	5915	150-380	26	395	280 - 510	3080	3280	-	3650	3820
VPX-25 620	6260	6345	160-380	28	395	280 - 510	3260	3480	-	3900	4100

